



For wire collated  
BDC nails



# BeA Pneumatic Nailer 830 DC

For nails: BDC 2.5 - 3.3 mm in the lengths of 50 - 83 mm

- Extremely powerful and sturdy
- Adjustable exhaust
- Integrated sound absorption
- Ergonomic handgrip, operator friendly
- Dust and dirt protection
- Reinforced nose piece
- Thread for mounting
- Tool body protection

## Applications

Siding / cladding, sheathing, sub flooring, pallets,  
boxes and cases, house construction



## BeA 830 DC

### Technical Data




Article code	12100457
EAN code	4045759047469
Magazine type	Top loader
Weight	3.8 kg
Dimensions in mm	L 307, H 361, B 132
Safety system	Contact actuation
Fastener type	Type BDC
Magazine capacity	max. 225 - 300 nails
Operating pressure	5 - 8 bar
Max operating pressure	8 bar
Air consumption/operation	3.68 litre / 6 bar
Inner hose diameter	9 mm recommended
Emission sound pressure level at the workstation	L <sub>pA, 1s, d</sub> = 94.8 dB
Single shot emission sound pressure level	L <sub>WA, 1s, d</sub> = 101.0 dB
Vibration level as per ISO 8662-11 is 3.12 m/s <sup>2</sup> .	
Accessories	Operating instructions, spare parts list, service instructions, allen wrench, oil, safety glasses

### Coil nails BDC

**BDC nails** = wire welded coil nails

Width	2.5 - 3.3 mm
Length	50 - 83 mm



BDC: 50 - 83 mm

Material	BK = steel, bright NK = steel, electro galvanized RF = stainless steel, comparable to material 1.4301 NR = stainless steel, comparable to material 1.4401 FV = steel, hot dipped galvanized
Surface properties	Smooth Ring shank Screw shank
Nail heads	Flat head Dome head Pozi head Torx head

Further types on request, nails conforming to DIN1052 and to EN 14592 (Eurocode 5)

BeA is a member of the following trade associations:



**WWW.ROZAGRAPISA.COM**