MINI COIL NAILER



drives $17 \sim 38$ mm $(11/16" \sim 11/2")$ flat plastic sheet collated nail

FEATURES Anti-double fire mechanism (UK Patent No. 2286790) The tool can be contact or single fired with no adjustments to tool. CONTACT FIRING SINGLE FIRING FIRING

Slim Contact Arm system (PAT. P)





CN238 enables nailing in corner just 6mm from the edge

Easy to access tight spots

APPLICATIONS Garden product Flooring Furniture case back TOOL SPECIFICATIONS MODEL CN238 WEIGHT 1.2kg (2.6 lbs) DIMENSIONS 249(H)×106(W)×217(L)mm 9-7/8"×4-3/16"×8-1/2" LOAD CAPACITY 200 nails (Plastic sheet collated nails) OPERATING PRESSURE 4~8kg/cm² (Regulator) 60~110 p.s.i. AIR CONSUMPTION 0.50 /cycle at 6 bar (90 p.s.i.) operating pressure A-weighted single-event sound power level

NOISE	LWA, 1s, d 94.1dB A-weighted single-event emission sound pressure level at work station LpA, 1s, d 75.1dB
	These values are determined and documented in accordance to CEN/TC 255 WG 1 N 45.3 E. (EN-standerd in preparation)
VIBRATION	Vibration characteristic value = 3.09m/s ² These values are determined and documented in accordance to ISO 8662-11

The specifications and design of the products in this catalog will be subject to change without advance notice due to our continuous efforts to improve the quality of our products.



MAX CO_,LTD_ 6-6 NIHONBASHI HAKOZAKI-CHO,CHUO-KU,TOKYO,JAPAN PHONE:81-3-3669-8131 FAX: 81-3-3669-7104 Web:http://www.max-ltd.co.jp/int/ Distributor:







17mm & 19mm nails

 Rear air exhaust system protects users

CE

- Built-in sound reducer lowers decibel level for quiet operation
 Special nose attachment for
- Special nose attachment for flooring application



