



BeA Hotmelt Applicator BeA 315

For hotmelt adhesive sticks Ø 43 mm

- Automatic temperature adjustment
- Very user friendly handling
- High security level due to stand-by function
- Electronic error indicator

Applications

Furniture and textile industry, upholstery applications



BeA 315

Technical specifications




| | |
|-----------------------------|---|
| Description | BeA 315 |
| Art No. | 12500186 |
| EAN-Code | 4045759056397 |
| Voltage / power consumption | 230 V / 400 W |
| Melting rate | 3,8 kg / 8 1/4 lbs / hour |
| Temperatur control | Electronic, exchangeable temperatur modules |
| Feed mechanism | manual |
| Temperatur range | 195° C / 380° F + moduls* 130°/ 160° / 215° |
| Operating pressure | - |
| Weight | 1,15 kg / 2 1/2 lbs |
| Cable length | 3 m / 10 ft |

Subject to technical changes

* optionally available

Hotmelt glue



| | |
|----------|---|
| Diameter | Ø 43 mm |
| Material | SP = Sprayable hotmelt glue based on Polyolefin |
| | HM = Hotmelt glue based on Ethylen-Vinylacetat |
| | PA = Hotmelt glue based on Polyamid |

BeA is member of the following associations:



Ungrap

ROZA-GRAPISA

www.rozagrapisa.com

López de Hoyos, 249 28043 Madrid
Ana María, 43 33209 Gijón (Asturias)

TI +34 914166614 +34 914167626 F +34 915193075
TI +34 985162833 F +34 985146622

email comercial@rozagrapisa.com
email asturias@rozagrapisa.com